




The bottom surface and the back of the amplifier are black lacquered on all models.



## Finishes

**AW440N**  Matt black

**AW440N**  Silver lacquered

**AW440N**  Gloss white lacquered RAL 9016



## Stereo - IcePower® based


<b>Power W RMS</b> 2 ch 4 Ω - 8 Ω	120 x 2 - 70 x 2
<b>Power W RMS</b> bridge 4 Ω - 8 Ω	440 x 1 - 240 x 1
<b>Input</b>	2 x RCA Unbalanced inputs
<b>Output connection</b>	Terminal blocks
<b>Max power consumption (W)</b>	520
<b>Low pass crossover</b>	40 Hz - 150 Hz 18 dB/oct
<b>Phase adjustment</b>	0° to 180°
<b>Bass boost frequency</b>	45 Hz, 0 dB to +6dB
<b>Signal to noise ratio (dBA)</b>	98
<b>Input sensitivity (V RMS)</b>	80 mV - 3,0 V
<b>Input impedance (Ω)</b>	47 K
<b>Power supply</b>	AC 230 V, 50 Hz
<b>Power-on modes</b>	Power switch
<b>Protection</b>	Thermal, Overcurrent
<b>Dimensions</b> H x W x D (cm)	6,0 x 10,0 x 25,5
<b>Weight (Kg)</b>	1,50

## Accessories

### Code: HKL044



2U Rack 19" frame supporting 4 amplifier modules



Dimensions  
H x W x D (cm)  
8,8 x 48,3 x 0,4

Weight (Kg) 0,25

### Code: HNL010



Blanking panel for HKL044



Dimensions  
H x W x D (cm)  
8,8 x 10,0 x 1,0

Weight (Kg) 0,30



This accessory is included in the package of AT440 and AW440 amplifiers.



Installation brackets

Dimensions H x W x D (cm)  
1,3 x 1,3 x 9,8

Weight (Kg) 0,10



Finishes



Specifiche tecniche



## Specifications

Specifiche  
Caractéristiques  
Spezifikationen

Link: [www.garvan.it/gat](http://www.garvan.it/gat)

